



FIXNORDIC.DK

# Pipe flashing Ø160x300 From FIXNORDIC



## DATASHEET

Pipe flashing Ø160x300  
From FIXNORDIC

## PRODUCT DESCRIPTION

### FIXNORDIC pipe flashing Ø160x300

Pipe flashing for safe penetration on the roof.

#### Application

Safe cable penetration for installations on roofs with roofing felt or foil membranes, through which cables can be pulled without obstacles from edges and protruding contours. Both the pipe and the top are equipped with an EPDM rubber edging. The top can be removed for easier adaptation of cables and pipes.

## ORDERING

Type	Article number
Pipe flashing Ø160x300 1-layer	220056-xxx
Pipe flashing Ø160x300 2-layers	230056-xxx
Article number – membrane code	
Find the membrane code under "Membrane overview" at <a href="http://fixnordic.dk">fixnordic.dk</a>	

## MATERIALS

Top:	Aluminium with EPDM rubber edge
Pipe:	Stainless steel EN 1.4401(AISI 316) with EPDM rubber edge
Flange:	Stainless steel EN 1.4301 (AISI 304)
Membrane:	The type of the integrated membrane must be specified to order

Installation and application must take place according to the latest industry instructions, and compatibility with the membrane of the roof must be ensured.

